

AD-A067 609

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO

F/G 21/4

A METHOD FOR TREATING THE ABSORPTION OIL, (U)

JUN 78 Y I GROMOV, I S SIDORENKO

UNCLASSIFIED

FTD-ID(RS)T-0915-78

NL

| OF |  
AD  
A067609



END  
DATE  
FILMED  
6-79  
DDC

AD-A067 609

FTD-ID(RS)T-0915-78

1


## FOREIGN TECHNOLOGY DIVISION



A METHOD FOR TREATING THE ABSORPTION OIL

by

Ye.I. Gromov, I.S. Sidorenko, et al



Approved for public release;  
distribution unlimited.

78 12 26 260

## EDITED TRANSLATION

FTD-ID(RS)T-0915-78

23 June 1978

MICROFICHE NR:

*FTD-78-C-000849*

A METHOD FOR TREATING THE ABSORPTION OIL

By: Ye.I. Gromov, I.S. Sidorenko, et al

English pages: 2

Source: USSR Patent No. 342889, 22 June 1972,  
pp. 1-2

Country of origin: USSR

Requester: FSTC

Translated by: Victor Mesenzeff

Approved for public release; distribution  
unlimited

NTIS	White Section	<input checked="" type="checkbox"/>
DDC	Buff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION		
BY		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AvAIL.	and/or SPECIAL
<i>A</i>		

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION  
FOREIGN TECHNOLOGY DIVISION  
WP.AFB, OHIO.

# U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<b>А а</b>	A, a	Р р	<b>Р р</b>	R, r
Б б	<b>Б б</b>	B, b	С с	<b>С с</b>	S, s
В в	<b>В в</b>	V, v	Т т	<b>Т т</b>	T, t
Г г	<b>Г г</b>	G, g	У у	<b>У у</b>	U, u
Д д	<b>Д д</b>	D, d	Ф ф	<b>Ф ф</b>	F, f
Е е	<b>Е е</b>	Ye, ye; E, e*	Х х	<b>Х х</b>	Kh, kh
Ж ж	<b>Ж ж</b>	Zh, zh	Ц ц	<b>Ц ц</b>	Ts, ts
З з	<b>З з</b>	Z, z	Ч ч	<b>Ч ч</b>	Ch, ch
И и	<b>И и</b>	I, i	Ш ш	<b>Ш ш</b>	Sh, sh
Й й	<b>Й й</b>	Y, y	Щ щ	<b>Щ щ</b>	Shch, shch
К к	<b>К к</b>	K, k	Ъ ъ	<b>Ъ ъ</b>	"
Л л	<b>Л л</b>	L, l	Ы ы	<b>Ы ы</b>	Y, y
М м	<b>М м</b>	M, m	Ь ь	<b>Ь ь</b>	'
Н н	<b>Н н</b>	N, n	Э э	<b>Э э</b>	E, e
О о	<b>О о</b>	O, o	Ю ю	<b>Ю ю</b>	Yu, yu
П п	<b>П п</b>	P, p	Я я	<b>Я я</b>	Ya, ya

\*ye initially, after vowels, and after ъ, ь; e elsewhere.  
When written as ё in Russian, transliterate as yě or ě.

## RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh <sup>-1</sup>
cos	cos	ch	cosh	arc ch	cosh <sup>-1</sup>
tg	tan	th	tanh	arc th	tanh <sup>-1</sup>
ctg	cot	cth	coth	arc cth	coth <sup>-1</sup>
sec	sec	sch	sech	arc sch	sech <sup>-1</sup>
cosec	csc	csch	csch	arc csch	csch <sup>-1</sup>

Russian	English
rot	curl
lg	log



## A METHOD FOR TREATING THE ABSORPTION OIL

Ye. I. Gromov, I. S. Sidorenko,  
V. N. Il'yashenko, P. G. Gus'kov,  
and B. I. Melikentsov.

The invention relates to the technique of purification of the absorption oil, used to remove the benzene hydrocarbons from the coke oven gas, from the impurities which cause corrosion in the equipment of the benzene department of the by-product coke industry.

There is a known method which uses a 25% solution of sulfuric acid for purifying the absorption oil from the organic (quinoline) bases, which, upon coming in contact with the hydrogen sulfide, hydrocyanic acid, and ammonium chloride contained in the coke oven gas, form the corrosion-active salts of organic bases. The acid solution of organic bases obtained in this case is subjected to further neutralization by the ammonia water.

The shortcoming of this method is in the fact that it requires the use of a corrosive 25% solution of sulfuric acid, which complicates the process due to the fact that the toxic acid solution of the bases cannot be discarded into the sewage.

For the purposes of simplification of the purification method for the absorbing oil and to prevent active corrosion of the equipment in the benzene department, it is proposed that the oil be treated with a mixture of the phlegm and separation water in the following composition:

	Phlegm water	Separation water
NH <sub>3</sub> volatile	0.06-0.09	0.09-0.12
NH <sub>3</sub> bonded	0.03-0.11	0.11-0.33
H <sub>2</sub> S	0.06-0.09	0.38-0.6
CN <sup>1</sup>	0.03-0.54	0.04-1.56
CNS <sup>1</sup>	0.03-0.05	0.06-0.1
Cl <sup>1</sup>	0.01-0.09	0.01-0.15
pH	7	7.2-7.8

The essence of the method consists of the fact that a portion of the absorbing oil (approximately 0.5-1.5 vol. %) in circulation from which benzene was removed is subjected to washing with a mixture of the phlegm and separation waters of the indicated composition. The ratio of oil and the wash water mixture is 1:4-1:2.

Corrosive thiocyanate, chlorine, and sulfurous compounds, formed out of the organic bases and the acidic admixtures of the coke oven gas, are eliminated during the washing process and a subsequent settling of the absorption oil. After it has been washed and separated from the water the oil is returned to circulation, while the water is mixed with the excess water used for final cooling of the coke oven gas and is directed to the area of purification.

**An example.** Oil in circulation is subjected to treatment at 3000-6000 l/h. As a result, during the 7 months of operation of the washer, the thiocyanate content in the absorption oil is decreased from 1030-1180 to 240 mg/l; the pH of the water extraction changes from 5 to 6.2; and the oil corrosion rate decreases from 15 down to 1 mm/g.

#### *Object of the invention*

The treatment method for the absorption oil, used to remove the benzene hydrocarbons from the coke oven gas by washing, is *distinguished* by the fact that, in order to simplify the process, the oil is washed with a mixture of the phlegm and separation waters.

Ukrainian Scientific Research  
Institute on Coal Chemistry

# DISTRIBUTION LIST

## DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>	<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	8	E403 AFSC/INA	1
C043 USAMIA	1	E404 AEDC	1
C509 BALLISTIC RES LABS	1	E408 AFWL	1
C510 AIR MOBILITY R&D	1	E410 ADTC	1
LAB/FIO		E413 ESD	2
C513 PICATINNY ARSENAL	1	FTD	
C535 AVIATION SYS COMD	1	CCN	1
C591 FSTC	5	ASD/FTD/NICD	3
C619 MIA REDSTONE	1	NIA/PHS	1
D008 NISC	1	NICD	2
H300 USAICE (USAREUR)	1		
P005 ERDA	1		
P005 CIA/CRS/ADB/SD	1		
NAVORDSTA (50L)	1		
NASA/KSI	1		
AFIT/LD	1		